Holm Security VMP | OnPrem
Network configuration guide

HOLM SECURITY

ⓘ **Information about the core machine & web access**

Web admin
Administrative user
User interface for implementation.
Web access: TCP ports 8001 (HTTPS)

Organizer*
Administrative user
Orchestration (multi-tenant) of Security Center.
Web access: TCP ports 8002 (HTTPS)

Security Center
End users
Web access: TCP ports 8004, 443 (HTTPS)

API documentation
Platform API: TCP port 8005 (HTTPS)

* If included in your license.

ⓘ **Scanner**
The Scanner Appliance performs the actual scans. Your license allows you to have any number of Scanner Appliances.

🌐 **Communication configuration**
Permit all traffic from the Scanner Appliance towards scan targets.

Scanner Appliance

Core system

Holm Security cloud

ⓘ **Updates and health checks**
Vulnerability tests and software updates are provided from Holm Security's cloud platform.

🌐 **Communication configuration**
Allow communication for the Scanner Appliance:
- Vulnerability test updates: TCP port 8007 (HTTPS)
- System patches (APT): TCP port 8044 (HTTPS)
- API for Scanner Appliance: TCP port 8004 (HTTPS)
- Scanner Appliance communication: TCP port 8022 (SSH)

🌐 **Communication configuration**
Allow vulnerability updates over:
- TCP port 443
- TCP port 8022

Allow communication outbound to:
- IPv4: 185.163.84.0/22
- IPv6: 2A0b:6800::/29